

Tri-County Free Fair

Mini Van Street Stock

General:

- Any American- made 1980's & newer mini vans ONLY
- Helmet, seat belt, long sleeves/pant and eye protection must be worn at all times on this track
- Vans must be stock
- No painting frame
- You may have a 12" x 12" roof sign that does not strengthen the vehicle in any way.
- Car must be swept clean of debri & glass before coming to event.
- Do not strip under the hood. Battery can be left in stock location. But you may put rubber mat over it or spray with foam around it NOT excessively. **Do not spray foam on anything else.**
- You may move the battery to the floor inside the van. You may lengthen the cables to reach the batter on the floor not the wiring harness.
- JUDGES DECISION IS FINAL. All cars are subjected to re-inspection at ANY time.

Van Build

- No cross breeding, entire drive must be same make as van (Chevy to Chevy, Ford to Ford and so on) Must have factory engine to car with stock exhaust.
1. Engine must be mounted with stock mounts in stock position.
 - **No welding of mounts. Must be bolted only.**
 2. No homemade cross members. Cross members must be stock and bolted in not welded.
 3. Doors may be fastened in 6 spots per door. 3/8" chain, #9 wire or 2" x 2" x 1/4" plates. If #9 wire is used then the wire from the bottom of the doors may go around frame.
 4. Trunks must be chained, wired or welded. No more than 6 spots. If welded (2" x 2" x 1/4" plates). If chained or wired they may go around bumper in 2 spots.
 - Vans must have deck lid/tailgate No welding or adding metal. Trunk lid must be in stock location. No tucking, wedging, pre-bending, smashing, folding or anything else you can think of. No welding washers for holes.
 5. Hoods may be chained or wired in 6 spots. You may use 5/16" chain or 2 strands of #9 wire per hole. It must be sheet metal to sheet metal only. No welding washers for holes. Must be 12" hole in hood in case of fire. Remove hood latch! Hood must be open for inspection.

6. Any tires permitted & double tires permitted. No foam filled tires and no valve stem protectors.
7. You may leave stock gas tank in stock location or you may relocate the fuel tank to rear floor of van, if this is done you must use a fuel cell or boat tank. **No stock fuel tanks allowed inside of van. Must only have 3 gallons of gas.**
8. Must remove windshields
9. NO CREASING ON THE BODY IS ALLOWED!!!
10. Stock type springs and shocks. No solid suspension. Screw in type risers are okay, no wire, chains or any weld on rear ends or rear spring pockets. Vans must bounce!!
11. You must use factory rear end for the van you are running.
12. You may weld spider gears in rearend to make it posi. No gears are allowed, you must use stock axles. You are not allowed to change the gear ratio or use aftermarket axles.

Bumpers:

13. You may ONLY use an 80 & Newer bumper on car. It must bolt on in the factory location and you may collapse the shocks and weld all the way around the shock and the plate to bumper. If car has no shocks bumper may be welded directly to frame with no metal added. Ends of bumpers must be open and NO added metal.
14. If the van has a wiring harness in front of the core support you may move it behind the core support.
15. All body bolts must be factory stock no altering permitted.

Judge's Decision are Final!

Thank you for taking the time to read the rules! Please build to the rules and we look forward to seeing all of you this 2023 season! Let's have some fun and put on a good show for the crowd!

If you have any questions, please contact:

Jesse Hamm
620-381-4762
Jwhamm@live.com